

READY-
TO-GOFROZEN
OR CHILL
MODE24/7
SERVICE

H/ACCP

EUROPEAN
UNION

OFFSHORE

The **PREMIUM**..range of refrigerated containers comes with the **HIGHEST** industry required specification and is the **ELITE** in our range. Built to the highest standard to provide reliable and consistent chilled or frozen temperatures for food transportation and storage. Our offshore containers are built and certified in accordance with DNV 2-7-1 and EN12079 offshore regulations and are CSC certified.



REFTRADE

RENTAL & SALES UK



Premium Specifications

- ❄️ Reliable and Efficient Machinery
- ❄️ S/S Butchers Door (Safety Release)
- ❄️ Non-Slip Chequered plate flooring
- ❄️ Dual Operation (Chill / Freeze)
- ❄️ Man Trap with visual and acoustic beacon
- ❄️ Emergency stop with Equipment Shut off
- ❄️ Internal LED Lighting
- ❄️ Heavy Duty Protection Frame
- ❄️ Material Traceability-Package
- ❄️ Comprehensive technical file

Available Options

- ❄️ Slings set (4 or 5 leg) - Certified
- ❄️ S/S Butchers Door (Safety Release)
- ❄️ Cargo Net / Chill Curtain
- ❄️ Two Compartments (Chill / Freeze)
- ❄️ Five Year Machinery Warranty
- ❄️ 4 tear heavy duty hygienic racking
- ❄️ Remote Monitoring Modem, RMM+

| Machinery | Electrical system | Connection | Cool / freeze Capacity | Temperature Range | Consumption |
|-----------|---|--|---|---------------------------------|-------------|
| Carrier | 380/460 V 50/60 Hz. 4P (3 Phase, Earth) | 32 Amp. 3hr. 380/460 V Fuse: 25 Amp. | at -29°C 3,2 kW at -18°C 4,9 - 6,6 kW at +2°C 9,4 - 12 kW | -25°C / +25°C < 38°C ambient | 16 Amp. |

ATEX Zone I or II, SELF-POWERED, REDUNDANCY or alternative machinery?

Check website for alternative Machinery Brochure.

| Model | Loading Capacity (Euro Pallets) | Int. dimensions (l. x w. x h.) mm. below load line | Ext. dimensions (l. x w. x h.) mm. | Door Opening (w. x h.) in mm. | Floor Surface | Capacity |
|-------|---------------------------------|--|---------------------------------------|---------------------------------------|--------------------|--------------------|
| 10' | 4 Max. Gross: 10.800 kg | 2,39 X 2,28 X 2,17 | 2,99 x 2,44 x 2,59 Tare: 2.980 kg. | 2,29 X 2,20 M. Pay load: 7.820 kg. | 5 M2 ² | 12 M2 ² |
| 20' | 10 Max. Gross: 14.200 kg | 5,36 x 2,33 x 2,21 | 6,06 x 2,44 x 2,59 Tare: 4.380 kg. | 2,26 X 2,20 M. Pay load: 9.820 kg. | 12 M2 ² | 28 M2 ² |